

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND COMPANY INFORMATION

Product Identification

- Trade Name: **Cure & Seal 250X**
- Product Use: Low VOC Cure and Seal for Concrete
- Restrictions on Use: Intended for industrial and professional users
- CAS#: Mixture

Company Information

- RussTech, Inc.
11208 Decimal Drive
Louisville, KY 40299
502-267-7700
- Prepared by Department of Environmental, Health and Safety

Emergency number – (served 24 hours)

- CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

Classification of substance or mixture:

Flammable liquid	Category 2	Highly Flammable liquid and vapor
Carcinogenicity	Category 1B	May cause cancer
Aquatic Hazard (acute)	Category 3	Harmful to aquatic life

Label elements: This material requires a hazard warning label in accordance with GHS criteria

Pictogram:



Signal Word: **DANGER**

Hazard statement(s):

H225: Highly Flammable liquid and vapor

H350: May cause cancer

H402: Harmful to aquatic life

Precautionary statement(s):

P201: Obtain special instructions before use

P202: Do not handle until all safety precautions have been read and understood

P280: Wear protective gloves/eye protection/face protection

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

CURE & SEAL 250X

Safety Data Sheet

P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion proof electrical/ventilating/lighting equipment
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P273: Avoid release to the environment
P280: Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353: IF ON SKIN (or hair): Remove immediately all clothing, rinse skin with shower or water
P308+P313: If exposed or concerned: Get medical advice
P370+P378: In case of fire use water fog, foam, dry chemical, or carbon dioxide (CO2) for extinction
P403+ P235: Store in well ventilated place. Keep cool.
P405: Store locked up
P501: Dispose of contents/container in accordance with local/state/federal regulations.

Hazards not otherwise classified:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Components:		
Chemical Name:	CAS#:	Content % by weight
Aromatic Petroleum Distillates	64742-95-6	3 – 7%
1,2,4-Trimethylbenzene	95-63-6	1 – 5%
Tert-Butyl Acetate	540-88-5	0.1 – 1%
Acetone	67-64-1	0.1 – 1%
Xylene	1330-20-7	0.1 – 1%
Cumene	98-82-8	0.1 – 1%

4. FIRST AID MEASURES

Inhalation: Move to fresh air. Respiratory tract irritant.

Eyes: Immediately flush eyes with water lifting upper and lower lids occasionally for 15 minutes.

Remove contact lenses if easy to do. Seek medical attention.

Skin: Remove contaminated clothing immediately. Wash affected area thoroughly with soap and water.

If irritation persists, seek medical attention. Wash contaminated clothes before re-use.

Ingestion: Rinse mouth. Contact physician or Poison Control Center (PCC) if you feel unwell

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Use water fog, foam, dry chemical, or carbon dioxide (CO2)

Unsuitable extinguishing media: Straight streams of water will scatter and spread fire

Specific hazards in case of fire: Prevent runoff. Use water spray to cool fire exposed surfaces. Vapors are flammable and heavier than air. Prevent build-up of vapors or gases. Flashback is a possibility.

Special protective equipment required for firefighting: SCBA (Self Contained Breathing Apparatus)

Additional information for firefighters: Incomplete combustion products, smoke, fume, oxides of carbon

CURE & SEAL 250X

Safety Data Sheet

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures:

- Ventilate closed spaces before entry
- Eliminate all ignition sources
- Wear appropriate PPE
- Keep unprotected persons away
- Use only non-sparking tools for cleanup and remediation

Environmental precautions:

- Avoid release to environment
- Prevent material from entering drains, septic systems, water sources, etc. using non-combustible dikes, absorbent materials, and booms.

Material containment and clean up:

- Contain material with dikes. Absorb with non-combustible material and put in closed container. Remove spilled material to storage for proper disposal. Dispose of in accordance with local, state, and federal regulations. See section 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions prior to use. Use PPE as required. Keep away from heat, sparks, open flames, and other ignition sources. No smoking. Use only with adequate ventilation. Prevent spills or leaks. Use proper bonding and grounding procedures. This material is a static accumulator. Prevent accumulation of static charge. Wash hands thoroughly after handling. Observe good industrial hygiene.

Information about protection against explosions and fires: Material and vapors are flammable. See section 5.

Information about safe storage: Store in original container. Keep container closed. Store in a cool dry well-ventilated area. Store locked up.

Shelf Life: 18 months

8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

Additional information about exposure controls: Adequate ventilation should be provided so that exposure limits are not exceeded. Mechanical ventilation or local exhaust ventilation may be required.

Chemical Identity	Type	Exposure Limit Values	Source
1,2,4 Trimethylbenzene	TWA	25 ppm 125 mg/m ³	US OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Acetone	TWA	250 ppm	US ACGIH Threshold Limits Values (03 2015)
Cumene	PEL	50 ppm 245 mg/m ³	US OSHA Table Z-1 Limits for air contaminants (29 CFR 1910.1000) (02-2006)
Xylene	TWA	100 ppm 435 mg/m ³	US OSHA Table Z-1 Limits for air contaminants (29 CFR 1910.1000) (02-2006)
Tert-Butyl Acetate	TWA	200 ppm	US ACGIH Threshold Limits Values (03 2015)

PPE (personal protective equipment) and hygienic measures:

- Observe good industrial hygiene practices
- Wear ANSI approved safety glasses or goggles to protect eyes
- Wear latex or rubber gloves to protect skin
- Wash hands thoroughly before breaks and at end of workday
- In case of inadequate ventilation use a suitable respirator

CURE & SEAL 250X

Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information:

- Physical state: Liquid
- Color: Clear
- Odor: Mild petroleum/solvent
- Odor Threshold: Not determined

Physical properties:

- pH value (@70°F): Not available
- Relative density: 1.05
- Boiling point: >95° F (>35° C)
- Freezing point/Melting point: Not available
- Decomposition temperature: Not available
- Vapor pressure: 9.5 hPa (70° F / 21° C)
- Vapor density: Vapors are heavier than air and may travel along floor and in bottom of containers
- Evaporation rate: slower than ether
- Solubility in / Miscibility with water: Practically insoluble
- Auto ignition: not available
- Flash point: 63°F / 17°C Method: Setaflash Closed Cup
- Lower / Upper Flammability Limits: Not available
- Viscosity: Not available

10. STABILITY AND REACTIVITY

Material reactivity: No data available

Material stability: Material is stable under normal conditions

Possibility of hazardous reactions: No data available

Incompatible materials to avoid: Strong oxidizers, strong acids, strong bases

Conditions to avoid: Heat, sparks, flame

Hazardous decomposition products: Thermal decomposition or combustion may liberate carbon dioxides and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Inhalation: In high concentrations, vapors, fumes, or mists may irritate nose, throat, and mucus membranes

Skin: May be harmful in contact with skin. Causes mild skin irritation

Eye: Eye contact is possible and should be avoided

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise

Acute Toxicity:

Oral (product) – no data available

Dermal (product) – ATEmix: 2,409.54 mg/kg

Inhalation (product) – no data available

Repeated dose (product) – no data available

Skin corrosion/irritation (product) – no data available

CURE & SEAL 250X

Safety Data Sheet

Serious eye damage/irritation (product) – no data available

Respiratory or Skin sensitization (product) – no data available

Carcinogenicity (product) – May cause cancer. Suspected of causing cancer

IARC Monographs on the Evaluation of Carcinogenic Risk to Humans

- Cumene – possibly carcinogenic to humans

US National Toxicology Program (NTA) Report on Carcinogens

- Cumene – reasonably anticipated to be a human carcinogen

Specific Target Organ Toxicity -Single Exposure / Repeat Exposure (product) – no data available

Cell Mutagenicity (product) – no data available

Reproductive toxicity (product) – no data available

Aspiration hazard (product) – no data available

12. ECOLOGICAL INFORMATION

The information is based on data available for the material, the components of the material and similar material.

Ecotoxicity: expected to be harmful to aquatic life

Biodegradation: no data available

Bioaccumulation potential / Bioconcentration Factor (BCF): no data available

Partition Coefficient n-octanol / water (log Kow): no data available

Mobility in soil: no data available

13. DISPOSAL CONSIDERATIONS

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Empty Container Warning: Empty containers may contain residue and can be dangerous. Do not reuse empty container. Do not expose empty containers to heat, sparks, static electricity, or other sources of ignition. Empty containers should be disposed of in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

Material is regulated for transport by land, air, and sea

UN1866, RESIN SOLUTION, 3, PG II

15. REGULATORY INFORMATION

- Sara 302 (extremely hazardous materials): not applicable
- Sara 311/312: Delayed health hazard, Fire hazard
- Sara 313: product includes a toxic chemical listed pursuant to EPCRA section 313 or 40 CFR Part 372 by weight:
 - 1,2,4-Trimethylbenzene (<5%), Cumene (<1%), Xylene (<1%)
- TSCA: All components are listed or exempt
- Sara 304: Emergency Release Notification / CERLA Hazardous Substances List (40 CFR 302.4)
 - Cumene 5000 lbs.
 - Methanol 5000 lbs.
 - Xylene 100 lbs.
 - Dimethyl Carbonate 100 lbs.
 - Acetone 5000 lbs.

CURE & SEAL 250X

Safety Data Sheet

- Tert-Butyl Acetate 5000 lbs.
 - Tert-Butyl Alcohol 100 lbs.
 - Ethylbenzene 1000 lbs.
- US California Proposition 65: This product contains Cumene, a chemical known by the state of California to cause cancer, birth defects or other reproductive harm
 - ⚠ **WARNING** Cancer and Reproductive Harm
 - www.P65Warnings.ca.gov
- VOC: Regulatory VOC (less water & exempt solvent): 320 g/l
- VOC Method 310: 7.11%

16. OTHER INFORMATION

This information is based on our current knowledge and is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of RussTech's knowledge or is obtained from sources believed by RussTech to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. RussTech assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, RussTech assumes no responsibility for injuries caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.