RUSSTECH

RussTech Form Retarder

RETARDER FOR VERTICALLY EXPOSED AGGREGATE SURFACES IN CONCRETE FORMS WITH NOMINAL DEPTH ETCH UP TO 1/4"

DESCRIPTION:

RUSSTECH FORM RETARDER is a non-flammable, 100% V.O.C. free, paintable gel designed for easy application to vertical concrete forms.

APPLICATION:

RUSSTECH FORM RETARDER should be used to create exposed aggregate surface, in contact with forms for stairs, walls and exposed aggregate panels to enhance the architectural beauty and to achieve a more slip-resistant surface.

DIRECTIONS FOR USE:

RUSSTECH FORM RETARDER should be applied without dilution to concrete forms up to two days in advance if sheltered from rain or in as short a time as two hours before use. Forms coated with RussTech Form Retarder have a slick and slimy feel along with a green color to let the applicator know where the product has been applied and that it is still active. Forms can be stripped in as little as 1 day in warmer weather or when accelerators are used, or in cold weather in 2 to 3 days. As with all concrete products, specific conditions in the field will dictate when forms should be removed and the mortar flushed to expose the aggregate.

PROTECT FROM FREEZING!

RECOMMENDED COVERAGE:

RUSSTECH FORM RETARDER should be applied at the rate of one gallon per 150 square feet by brush or roller.

A high quality cure and seal such as **RUSSTECH CURE & SEAL 300**, **CRETESEAL 30 or STAMPSEAL 30** is recommended for use on exposed aggregate to enhance the natural appearance while protecting it from staining, exposure to freeze-thaw cycles and commonly used de-icing chemicals.

WARRANTY:

RussTech Inc. guarantees RUSSTECH FORM RETARDER to be free of contaminants and to perform as described when used according to the directions. All information herein is believed to be true and accurate and is presented in good faith. RussTech, its agents and distributors assume no responsibility for any risks or liability which may arise from either use or performance of this product since conditions, applications and the capabilities of applicators are beyond our control.

PACKAGING:

Available in: 1-gallon containers 4 per case

VISIT US ON THE WEB AT:

www.RussTechnet.com

SHELF LIFE:

18 months

