

---

# RUSSTECH<sup>®</sup>

---

## THE BEAN<sup>™</sup>

### CONCRETE AND WOOD WATER REPELLENT

*“The environmentally safe way to seal wood and concrete surfaces.”*



#### DESCRIPTION:

**THE BEAN<sup>™</sup>** produces a satin to transparent finish on wood surfaces and a transparent finish on concrete surfaces. This patented formula is designed to penetrate the pores of concrete and wood surfaces from which it quickly disperses water. This method of protection **does not bead water**.

**THE BEAN<sup>™</sup>** has little or no harmful odor. This product is the most environmentally friendly of its kind. Overspray will not harm plants or animals. Time is saved by not having to cover plants or applying by roller. When applied according to label instructions, this product will provide 1 year protection for wood and 2 years protection for concrete surfaces.

#### FEATURES:

**THE BEAN<sup>™</sup>** is a fresh alternative to the typical sealers on the market. The product is probably the most environmentally safe brought to market so far. Its main ingredient- soybean oil- is absolutely harmless to plants and animals.

**THE BEAN<sup>™</sup>** does not qualify as a curing compound; however, when curing blankets or plastics are being used, an application of **THE BEAN<sup>™</sup>** has been found to minimize or eliminate discoloration of all regular and pervious concrete surfaces due to condensation lines (tiger stripes) from being covered with plastic or curing blankets.

#### APPLICATIONS:

##### Concrete Surfaces:

- Pervious concrete (can be used as an additional guard against rapid surface evaporation prior to the plastic 7-day cover).
- Driveways
- Sidewalks
- Pool decks
- Dog kennels
- Outdoor furniture
- Stamped concrete surfaces
- Eco-Friendly Bond Breaker

##### Wood Surfaces:

- Decks
- Docks
- Fences
- Playground equipment
- Outdoor furniture
- Picnic tables
- Gazebos
- Pergolas

#### PREPARATION:

- Wood  
Remove any residual membrane sealer from the surface to be treated.  
New pressure treated lumber should be lightly pressure washed after thirty days.  
Allow 60 days before freshly stained wood is treated.
- Concrete  
Remove any residual membrane sealer or curing compound from the surface to be treated.  
Allow the concrete surface to dry.  
Remove all oil stains.

## **DIRECTIONS FOR USE:**

**THE BEAN™** is a ready to spray mixture and thinning shouldn't be necessary. Choose a day with a 24 hour rain free window of weather. Because the product is water-based, a hard rain could re-emulsify the oil and dilute the protection. Stir or agitate product thoroughly prior to application.

Product that has been stored longer than six months may require more agitation.

When using a garden sprayer, apply lightly at first and let the material penetrate the surface. A second light application may be applied if desired.

**THE BEAN™** should initially leave a yellow milky film which is the natural color of the soybean oil. This will disappear as the material penetrates the surface. Areas where coverage is too heavy can be rolled or wiped away with a clean rag to avoid a slipping hazard.

## **COVERAGE OF SURFACES:**

Coverage depends on surface porosity. Typical coverage for an aged wood deck is ~100 ft<sup>2</sup>/gal, and 200 ft<sup>2</sup>/gal for exterior broom-finished concrete. Depending on ambient and surface conditions, a typical 70 degree day with 70% humidity could need from 45-90 minutes before being subjected to foot traffic. Automobile traffic is allowed when the surface is completely dry.

All information provided herein is believed to be true and accurate and is presented in good faith. RussTech, its agents and distributors assume no responsibility for any risks or liability which may arise from either the use or performance of this product since conditions, applications and capabilities of the applicators are beyond our control.



## **LIMITATIONS:**

RussTech and C2 Products, Inc. shall not be held liable for the safety of any person handling, using or storing this product. The use of the product is a single component of a field manufactured end product and therefore C2 Products, Inc. issues no warranty of any kind, expressed or implied.

This product is by nature a lightweight oil and should not be expected to stop heavier oils (e.g., motor oil) from penetrating into the concrete.

## **CLEAN-UP:**

**THE BEAN™** cleans up with soap and water, so please store it where it will not freeze.

## **STORAGE:**

**THE BEAN™** is non-flammable, biodegradable, non-toxic, has no V.O.C.'s, and is extremely environmentally friendly.

## **PACKAGING:**

**THE BEAN™** is available in 5 gallon pails and one gallon jugs.

## **SHELF LIFE:**

12 months

## **VISIT US ON THE WEB AT:**

[www.RussTechnet.com](http://www.RussTechnet.com)

[www.C2products.com](http://www.C2products.com)



**RussTech Inc.**

"We Add The Difference"